

XS2so/XS4so Dual Channel Solid-State Safety Output Modules




Datasheet

Models

Model	Description
XS2so	2 Dual Channel Solid-State Safety Output Module
XS4so	4 Dual Channel Solid-State Safety Output Module

Terminal Assignment



Specifications

Mechanical Stress

Shock: 15 g for 11 ms, half sine, 18 shocks total (per IEC 61131-2)
 Vibration: 3.5 mm occasional / 1.75 mm continuous at 5 Hz to 9 Hz,
 1.0 g occasional and 0.5 g continuous at 9 Hz to 150 Hz: all at 10
 sweep cycles per axis (per IEC 61131-2)

Safety

Category 4, PL e (EN ISO 13849)
 SIL CL 3 (IEC 62061, IEC 61508)

Product Performance Standards

See Standards and Regulations section in the Instruction Manual for a
 list of industry applicable U.S. and international standards

EMC

Meets or exceeds all EMC requirements in IEC 61131-2, IEC 62061
 Annex E, Table E.1 (increased immunity levels), IEC 61326-1:2006,
 and IEC61326-3-1:2008

Solid State Safety Outputs

XS2so: 0.75 A max. at 24 V dc (1.0 V dc max drop)
 XS4so: 0.5 A max. at 24 V dc (1.0 V dc max drop)
 Inrush: 2 A max.
 Output Off threshold: 1.7 V dc typical (2.0 V dc max.)
 Output leakage current: 50 µA max. with open 0 V
 Load: 0.1 µF max., 1 H max., 10 Ω max. per lead

Safety Ratings

PFH [1/h]: 5.8×10^{-10}
 Proof Test Interval: 20 years

Certifications



Feature ID (FID) Compatibility

For Feature ID (FID) compatibility between a Base Module and the
 Expansion Modules, see XS26-2/SC26-2 Base Safety Controllers
 datasheet p/n 175119.



Important: The Safety Controller and all solid state output expansion modules should be connected only to a SELV (Safety Extra-Low Voltage), for circuits without earth ground or a PELV (Protected Extra-Low Voltage), for circuits with earth ground power supply.

Operating Conditions

Temperature: 0 °C to +55 °C (+32 °F to +131 °F)
 Storage Temperature: -30 °C to +80 °C (-34 °F to +176 °F)

Environmental Rating

NEMA 1 (IEC IP20), for use inside NEMA 3 (IEC IP54) or better
 enclosure

Removable Screw Terminals

Wire size: 24 to 12 AWG (0.2 to 3.31 mm²)
 Wire strip length: 7 to 8 mm (0.275 in to 0.315 in)
 Tightening torque: 0.565 N·m (5.0 in-lb)

Removable Clamp Terminals

*Important: Clamp terminals are designed for 1 wire only. If more than
 1 wire is connected to a terminal, a wire could loosen or become
 completely disconnected from the terminal, causing a short.*
 Wire size: 24 to 16 AWG (0.20 to 1.31 mm²)
 Wire strip length: 8.00 mm (0.315 in)

External Power

XS2so: 24 V dc ± 20% (including ripple); 0.075 A no load, 3.075 A
 max. load
 XS4so: 24 V dc ± 20% (including ripple); 0.1 A no load, 4.1 A max.
 load
 Maximum Power-up Delay: 5 seconds after the Base Controller
 Limited Isolation: ±30 V dc max. referenced to 0 V on the Base
 Controller

Bus Power

0.02 A

Test Pulse

Width: 200 µs max.
 Rate: 200 ms typical

Output Protection

All solid-state outputs (safety and non-safety) are protected from
 shorts to 0 V or +24 V, including overcurrent conditions

Banner Engineering Corp. Limited Warranty

Banner Engineering Corp. warrants its products to be free from defects in material and workmanship for one year following the date of shipment. Banner Engineering Corp. will repair or replace, free of charge, any product of its manufacture which, at the time it is returned to the factory, is found to have been defective during the warranty period. This warranty does not cover damage or liability for misuse, abuse, or the improper application or installation of the Banner product.

THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), AND WHETHER ARISING UNDER COURSE OF PERFORMANCE, COURSE OF DEALING OR TRADE USAGE.

This Warranty is exclusive and limited to repair or, at the discretion of Banner Engineering Corp., replacement. IN NO EVENT SHALL BANNER ENGINEERING CORP. BE LIABLE TO BUYER OR ANY OTHER PERSON OR ENTITY FOR ANY EXTRA COSTS, EXPENSES, LOSSES, LOSS OF PROFITS, OR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES RESULTING FROM ANY PRODUCT DEFECT OR FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER ARISING IN CONTRACT OR WARRANTY, STATUTE, TORT, STRICT LIABILITY, NEGLIGENCE, OR OTHERWISE.

Banner Engineering Corp. reserves the right to change, modify or improve the design of the product without assuming any obligations or liabilities relating to any product previously manufactured by Banner Engineering Corp. Any misuse, abuse, or improper application or installation of this product or use of the product for personal protection applications when the product is identified as not intended for such purposes will void the product warranty. Any modifications to this product without prior express approval by Banner Engineering Corp will void the product warranties. All specifications published in this document are subject to change; Banner reserves the right to modify product specifications or update documentation at any time. Specifications and product information in English supersede that which is provided in any other language. For the most recent version of any documentation, refer to: www.bannerengineering.com.